

IN THE CLAIMS:

The claims, as pending in the subject application, now read as follows:

1. (Currently amended) An information processing apparatus generating print data sent to a printer, comprising:

a first display unit configured to display a first setting screen to set an entire color mode defining a color mode to be applied to the entire document data;

a second display unit configured to display a second setting screen to set a chapter color mode defining the color mode to be applied to a selected chapter including a plurality of pages of the document data, wherein the second setting screen is a window different from the first setting screen;

a third display unit configured to display a third setting screen to set a page color mode defining the color mode to be applied to a selected page of the document data, wherein the third setting screen is a window different from the first setting screen and the second setting screen; [[and]]

a determining unit configured to determine whether the printer can change a print mode in processing of the print data based on performance information of the printer acquired from the printer before the print data is sent; and

a print data generating unit configured to generate print data including a color mode changing command so that a printer prints a printed material on which the color mode defined by the page color mode is applied to the selected page and the color mode defined by the chapter color mode is applied to the selected chapter and the color mode defined by the entire color mode is applied to the remaining portion of the document data to which the page color

mode and the chapter color mode are not applied when the determining unit determines that the printer can change the print mode in processing of the print data, the entire color mode is set in accordance with an instruction received via the first setting screen displayed by said first display unit, [[and]] the chapter color mode is set in accordance with an instruction received via the second setting screen displayed by said second display unit and the page color mode is set in accordance with an instruction received via the third setting screen displayed by said third display unit.

2. and 3. (Canceled)

4. (Previously presented) The apparatus according to Claim 1, wherein said printing data generating unit determines whether the printer copes with a change of the color mode before the print data containing the instruction of changing the color mode is generated by using a generating function to generate the print data, when the printer copes with the change, generates, by using the generating function, printing data containing the instruction of changing the color mode, and when the printer does not cope with the change, generates, by using the generating function, print data containing no instruction of changing the color mode.

5. to 10. (Canceled)

11. (Currently amended) A print data generating method sent to a printer, comprising:

a first display step of displaying a first setting screen to set an entire a color mode defining a color mode to be applied to a the entire document data;

a second display step of displaying a second setting screen to set a chapter color mode defining the color mode to be applied to a selected chapter including a plurality of pages of the document data, wherein the second setting screen is a window different from the first setting screen;

a third display step of displaying a third setting screen to set a page color mode defining the color mode to be applied to a selected page of the document data, wherein the third setting screen is a window different from the first setting screen and the second setting screen; [[and]]

a determining step of determining whether the printer can change a print mode in processing of the print data based on performance information of the printer acquired from the printer before the print data is sent; and

a print data generating step of generating print data including a color mode changing command so that a printer prints a printed material on which the color mode defined by the page color mode is applied to the selected page and the color mode defined by the chapter color mode is applied to the selected chapter and the color mode defined by the entire color mode is applied to the remaining portion of the document data to which the page color mode and the chapter color mode are not applied when the determining step determines that the printer can change the print mode in processing of the print data, the entire color mode is set in accordance with an instruction received via the first setting screen displayed in said first display step, [[and]] the partial color mode is set in accordance with an instruction received via the second setting

screen displayed in said second display step and the page color mode is set in accordance with an instruction received via the third setting screen displayed in said third display step.

12. and 13. (Canceled)

14. (Previously presented) The method according to Claim 11, wherein, in the print data generating step, whether the printer copes with a change of the color mode is determined before the print data containing the instruction of changing the color mode is generated by using a generating function to generate the print data, when the printer copes with the change, print data containing the instruction of changing the color mode is generated by using the generating function, and when the printer does not cope with the change, print data containing no instruction of changing the color mode is generated by using the generating function.

15. to 20. (Canceled)

21. (Currently amended) A computer-readable medium storing a printing control program, which causes a computer to perform a print data generating method of generating print data sent to a printer, said method comprising:

a first display step of displaying a first display screen to set an entire color mode defining a color mode to be applied to the entire document data;

a second display step of displaying a second setting screen to set a chapter color mode defining the color mode to be applied to a selected chapter including a plurality of pages of

the document data, wherein the second setting screen is a window different from the first setting screen;

a third display step of displaying a third setting screen to set a page color mode defining the color mode to be applied to a selected page of the document data, wherein the third setting screen is a window different from the first setting screen and the second setting screen; [[and]]

a determining step of determining whether the printer can change a print mode in processing of the print data based on performance information of the printer acquired from the printer before the print data is sent; and

a print data generating step of generating print data including a color mode changing command so that a printer prints a printed material on which the color mode defined by the page color mode is applied to the selected page and the color mode defined by the chapter color mode is applied to the selected chapter and the color mode defined by the entire color mode is applied to the remaining portion of the document data to which the page color mode and the chapter color mode are not applied when the determining step determines that the printer can change the print mode in processing of the print data the entire color mode is set in accordance with an instruction received via the first setting screen displayed in said first display step, [[and]] the partial color mode is set in accordance with an instruction received via the second setting screen displayed in said second display step and the page color mode is set in accordance with an instruction received via the third setting screen displayed in said third display step.

22. and 23. (Canceled)

24. (Previously presented) The computer-readable medium storing a printing control program according to Claim 21, wherein in the print data generating step, whether the printer copes with a change of the color mode is determined before the print data containing the instruction of changing the color mode is generated by using a generating function to generate the print data, when the printer copes with the change, print data containing the instruction of changing the color mode is generated by using the generating function, and when the printer does not cope with the change, print data containing no instruction of changing the color mode is generated by using the generating function.

25. to 30. (Canceled)

31. (Previously presented) The apparatus according to Claim 1, wherein the entire color mode is set for specifying whether color printing or monochrome printing is performed for the entire document data, and the partial color mode is set for specifying whether color printing or monochrome printing is performed for the predetermined unit of the document data.

32. (Previously presented) The method according to Claim 11, wherein the entire color mode is set for specifying whether color printing or monochrome printing is performed for the entire document data, and the partial color mode is set for specifying whether color printing or monochrome printing is performed for the predetermined unit of the document data.

33. (Previously presented) The computer-readable medium storing a printing control program according to Claim 21, wherein the entire color mode is set for specifying whether color printing or monochrome printing is performed for the entire document data, and the partial color mode is set for specifying whether color printing or monochrome printing is performed for the predetermined unit of the document data.